



Fire Apparatus Quotation for: METROPOLITAN AREA PLANNING COUNCIL



Quotation Number: 94885 Rev: 9

Unit Description: PMPR-COMM

Quote Description: Pumper, Commercial Chassis

Salesperson: AJACONETTI

Salescode	Extended Description	Qty	
TESTING COMPLIANCE STANDARD			
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3090-0007	Hosebed hoseload allowance on the apparatus shall be 1200 lbs.	1	
3340-1137-12B	Equipment allowance on the apparatus shall be 2000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
CHASSIS PREP			
1020-0011	Commercial Chassis Prep for E-1supplied International chassis	1	
BUMPERS			
1160-0004	Stainless Steel 10" high front bumper. Requires extended front bumper.	1	
1160-0008	3/16" Front Bumper Gravel Shield.	1	
1160-0014	20" Front Bumper Gravel Shield Extension.	1	
BUMPER TRAYS			
1150-0055	Hinged diamond plate lid for center bumper tray. Includes: seal, 1/4 turn latch and gas shock hold open device.	1	
1150-0159	Bumper tray center of bumper with slats 16 inches deep (approx 15 inches to slats).	1	
WHEEL OPTIONS			
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1	

Salescode	Extended Description	Qty	
WHEEL OPTIONS			
1050-0008	Rear axle (single) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1	
TIRE OPTIONS			
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1	
AIR SYSTEM OPTIONS			
1110-0010-277	Air inlet. To charge brake system. Commercial chassis only. Location: driver's door step area.	1	
1110-0027	Isolated air tank. Includes pressure protection valve.	1	
1110-0187	Auxiliary air tank to be plumbed to the air primer.	1	
ENGINES & TRANSMISSIONS			
1200-0126	Commercial chassis speed to be electronic limited and not to exceed a maximum of 68 MPH. Note: Speed rating may be lower based on OEM tire ratings/top speed limitations provided on chassis.	1	
1200-0358	Cummins L9 engine, 330 HP @ 2000 RPM, 1000 lb-ft Torque @ 1300 RPM, 2200 RPM Governed Speed	1	
CHASSIS OPTIONS			
1680-0011	Tow eyes rear below body, painted.	1	
1680-0042	Tow hooks front painted in the down position.	1	
1680-0426	E-ONE built diamond plate trim package for 4 door commercial chassis cab. Includes mounting surface for the battery charger receptacle, display, air inlet, etc(as applicable).	1	
CAB MODEL			
1520-0203	Four door International MV607 4x2.	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0227	Reflective striping shall be installed on commercial cab doors, visible when the door is open, meeting NFPA requirement of 96 sq. in. coverage for each door.	1	
MISC EXTERIOR CAB OPTIONS			
1675-0007	Diesel fuel only label.	1	

Salescode	Extended Description	Qty	
SEATS			
1510-0151	Universal air pack bottle bracket installed (EA).	4	
1685-0032	Seating capacity tag of five occupants.	1	
MISC INTERIOR CAB OPTIONS			
1685-0073	Control lanyard Y type or dual single pull as applicable for air horns on a commercial chassis.	1	
1685-0450	Center control console painted black Zolatone. Locate in cab between driver and officer. Includes area for NFPA siren, electrical, and in-cab controls (as applicable) switching.	1	
CAB ELECTRICAL OPTIONS			
1750-0022	Battery charger Kussmaul 40 amp model 1200 with air compressor.	1	
1750-0059-277-04	Receptacle inlet 20 amp with a Yellow cover. Location: driver's door step area.	1	
1750-0073-585	Antenna base Tessco P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: driver side forward with coaxial cable terminating at the center of the dash board.	1	
1750-0073-587	Antenna base Tessco P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: officer side forward with coaxial cable terminating at the center of the dash board.	1	
BODY COMPT LEFT SIDE			
3100-0096	Driver side body with full height 42" wide forward and 42" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well.	1	
BODY COMPT RIGHT SIDE			
3120-0005	Officer half side body with 42" wide forward and 42" wide rearward compartmentation. Includes adjustable ladder tracks.	1	
BODY COMPT REAR			
3110-0005	Full Height Rear Compartment. Includes smooth plate panels.	1	
3110-0034	Upper rear compartment depth to be shallow.	1	
3340-0116	Bolt-on diamond plate 14" tailboard (full width of body). Includes (2) squared off beavertails (no stanchions) with removable outer panels and handrails- (2) vertical on trailing edge of body and horizontal mounted handrail(s) below hosebed.	1	
DOORS			
3300-0105-003	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): L1.	1	
3300-0105-005	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): L3.	1	

Salescode	Extended Description	Qty	
DOORS			
3300-0105-027	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): B1.	1	
3300-0106-004	Door roll up short (up to 45") with satin finish Amdor. Location(s): L2.	1	
3300-0106-015	Door roll up short (up to 45") with satin finish Amdor. Location(s): R1.	1	
3300-0106-016	Door roll up short (up to 45") with satin finish Amdor. Location(s): R2.	1	
COVERS			
3305-0003	Single diamond plate cover for the crosslay area. Includes applicable grab handle(s) and (2) butterfly style latches.	1	
3305-0004	Crosslay cover to be hinged forward.	1	
3305-0023	Nylon black cargo net at rear of diamond plate or vinyl hose bed cover or similar.	1	
3305-0025	Nylon black cargo net on sides for crosslay cover.	1	
3305-0033	Vinyl access cover for fill tower(s).	1	
3305-0034-000-02	Vinyl Red hose bed cover without rear flap(s). Requires rear cover option.	1	
3305-0119	Hold open device(s) for aluminum crosslay (single or bi-fold) cover. Locate as required based off options on module.	1	
PUMP MODULE			
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and tranverse module(s) if applicable.	1	
3130-0523	Side mount pump module. Extruded aluminum with runningboards.	1	
3130-0532	Pump panel opening is 39" wide. Pumper / tanker only.	1	
3130-0539	Pump module height is 75". Pumper / tanker only.	1	
PUMP PANELS			
3134-0016	Stainless steel driver and officer side pump panels.	1	
3134-0143	Officer side pump panel to be vertical hinged on forward extrusion. Panel to be (3) pieces with upper (2) panels secured in the closed position with push button latches. Upper panel to be held open with gas shock.	1	
MISC PUMP PANEL OPTIONS			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
PUMP MODULE OPTIONS			
3136-0000-202	Air horn switch at pump panel. Switch to be labeled "Evacuation Alert". Location: driver side pump panel.	1	
3136-0010	Stainless steel roller assemblies for crosslays and/or speedlays.	1	

Salescode	Extended Description	Qty	
PUMP MODULE OPTIONS			
3136-0011	P-Rubber in flex joint(s) between pump module and/or body modules.	1	
3136-0012	Slat flooring. The crosslay and/or speedlays are to have removable slat flooring.	1	
3136-0058	E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels.	1	
3136-0138	Pump module storage pan.	1	
3136-0139	Crosslay double 7.5" wide each to hold up to 200' of 2.0" DJ hose (each).	1	
WATER TANK			
4010-0099	Fill tower(s) to be located offset to officer side of water tank.	1	
4010-0176	780 Gallon "T" Water Tank. UPF Poly III color fill towers. Note: Any foam cell(s) and/or storage options through the tank will reduce the overall water capacity.	1	
TANK PLUMBING			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0119	3" tank to pump Akron manual valve w/4" tank connection.	1	
LADDER STORAGE / RACKS			
3365-0025-515	Attic ladder mounting brackets (PR). Locate officer side compartment top.	1	
3365-0028	Hard Suction Storage Rack. Driver side compartment top. Includes spring hold downs and scuff plates behind spring mounts (as applicable).	1	
3365-0031	Hard Suction Storage Rack. Officer side in adjustable track above ladders (if applicable). Includes spring hold downs and scuff plates.	1	
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1	
3365-0087-C57	The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder.	1	
HANDRAILS / STEPS			
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
3330-0278	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on officer side (staggered stepped as applicable with tailboard depth) for additional hosebed access and handrail mounted on officer side upper hosebed side (as applicable).	1	
MISC BODY OPTIONS			
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover	1	

Salescode	Extended Description	Qty	
MISC BODY OPTIONS			
	plate work (as applicable). Hosebed adjustable divider extrusion in the forward area and rearward area of the hose bed to run full width of the hosebed (as is practical with other hosebed mounted equipment).		
3340-0035	Divider Long. To run full length of hose bed (front to rear).	2	
3340-0074	Body mainframe and hosebed side assemblies for a 85" high body.	1	
3340-0089-000-13	Turtle Tile Brand Black Floor Matting covering all applicable Compartment Floors, Shelves, and Rollout Trays. Does not include roof top compartments (Added separately)	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0486	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes.	1	
3340-0680	Body mainframe layout line to be 23". Includes body and all applicable modules.	1	
3340-1648	Anodized aluminum trim on bottom edge of all body compartment openings with painted edge.	1	
SCBA BOTTLE STORAGE			
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
3320-0185-497	Fire Shopp brand (1) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location:driver side rear wheel well offset rearward	1	
3320-0186-498	Fire Shopp brand (2) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Location:officer side rear wheel well offset forward	1	
3320-0186-500	Fire Shopp brand (2) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Location:officer side rear wheel well offset rearward	1	
3320-0188-495	E-ONE designed Wheel Chock storage compartment driver side rear wheel well offset forward with hinged door and push button latch and wired to "Door Open" indicator inside cab. Door material to match wheel well material. Storage area shall hold (2) Zico Model SAC-44-E or comparable Wheel Chocks (not included).	1	
PUMPS			
4005-0030	Rating 1250 GPM	1	

Salescode	Extended Description	Qty	
PUMPS			
4005-0195	Hale QFLO 750-1250 GPM pump, single stage. Requires primer option.	1	
PUMP CERTIFICATION			
4475-0000	Pump certification 750-2250 GPM	1	
PUMP OPTIONS			
4015-0008	Zinc anodes for Hale pump (PR), (1) discharge side and (1) intake side.	1	
4015-0016	Thermal relief valve, Hale TRVL-120.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0098	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location on pump panel.	1	
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1	
4015-0242	Trident primer W/3 barrel push button control. For use with 1250 GPM and larger pumps. Requires 15.6 CFM or larger engine air compressor.	1	
INTAKES			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	
INTAKE OPTIONS			
4445-0009	Intake relief valve, Akron.	1	
DISCHARGES AND PRECONNECTS			
4415-0008	1.5" Front bumper discharge Akron manual valve.	1	
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1	
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1	
4415-0022-350	2.5" Left Rear Discharge Akron Manual Valve. Location: left rear discharge.	1	
4415-0041	3" Deck Gun Discharge, Akron manual valve. (outlet shall terminate with MNPT threads unless extend gun is install)	1	
4415-0054-583	4" Right Pump Panel Discharge with 3" Akron Manual Valve (Waterous pumps noted location to be forward lower port). Location: right side discharge 1.	1	
4415-0178-532	Polished Stainless Steel Swivel Located on Top of Bumper officer's side of center	1	

Salescode	Extended Description	Qty	
DISCHARGES AND PRECONNECTS			
	tray for Front Bumper Discharge.		
4417-0106-L65	Deck gun piping to be positioned centered in deck gun channel.	1	
DISCHARGE OPTIONS			
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1	
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	9	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	
4417-0246	Dealer installed monitor, make and model as specified.	1	
PRESSURE GOVERNORS			
4465-0020	Class 1 TPG Plus pressure governor. Includes master intake and discharge gauges, water, oil, volt and tachometer.	1	
GAUGES			
4435-0001	Class 1 Intelli-Tank water tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	9	
ELECTRICAL SYSTEMS			
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1	
5010-0052-1NI	Vista IV touch screen display for V-MUX electrical system. Location: center console, mounted on a Panavise Swivel Arm Mounting Option Weldon C624 series brkt to allow clear sight from either driver or officer positions.	1	
5010-0053	Vehicle data recorder for commercial cab - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
LIGHT BARS			
5300-0504	Whelen MKEZ7 1.5" standard mount for front light bar (PR).	1	
5300-0506-000-4V	Front light bar LED color: Red/White with clear lenses (If applicable, includes side facing when colors are the same.)	1	
5300-0522	Light bar Whelen Freedom IV Model F4X0 60" with 8 LED modules. Location: Centered on the front cab roof.	1	
WARNING LIGHT PACKAGES			
5550-0486-535-4U	Whelen Super LED lower level warning light package. Includes (6) C-Series	1	

Salescode	Extended Description	Qty	
WARNING LIGHT PACKAGES			
	model C6L light heads and (4) ION-T Series model TLI light heads with bezels. Color: Red with red lenses. Locate side facing lights: at forward most position, centered in rear wheel well, and side facing at rear of body in rubrail if equipped. Note: ION-T Series light only available with clear lenses.		
WARNING LIGHTS			
5600-0080-479-06	Whelen beacon with LED upper beacon and 700 series Super LED (PR) model B6LED with red domes and Red LEDs. Location: rear upper body on aerial style brackets.	1	
5600-0105-B13	Hazard (door ajar) light 2" LED. Location: center console.	1	
SIRENS			
5500-0012	Prewire for Federal Q2B mechanical siren. Driver side front bumper.	1	
5500-0015	Whelen model 295SLSA1 siren with microphone (replaced 295HFSA1).	1	
5500-0024-B13	The primary electronic siren control is to be located center console.	1	
SPEAKERS			
5510-0029-209	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper.	1	
DOT LIGHTING			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0022	Marker light LED body package. Commercial pumper bodies only.	1	
5150-0215	Whelen C6 series LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical chrome ABS 4 housing and weatherproof connectors.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0276	Compartment light package TecNiq T440 4" LED for small bodies.	1	
5380-0280	Ground light package TecNiq T440 4" LED - large.	1	
LIGHTS - DECK AND SCENE			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0215-395	Deck Lights - Optronics Model TLL44 (PR). Location: rear body/beavertail area on the trailing edge up high.	1	
5390-0216	Hose bed light Optronics LED model TLL44 Locate at front of hose bed. Switched with work light switch in cab.	1	

Salescode	Extended Description	Qty	
LIGHTS - DECK AND SCENE			
5390-0217	Crosslay light Optronics LED model TLL44. Locate to rear of crosslay (SM) and forward of crosslay (TM as applicable). Switched with work light switch in cab.	1	
LIGHTS - NON-WARNING			
5400-0003	Engine compartment light (EA).	1	
5400-0011	LED pump compartment light (EA).	1	
5400-0031	Pair of Cab Dome Large Lights mounted driver and officer side front. N/A on E-One Chassis. Required on Comm Chassis.	1	
5400-0032	Pair of Cab Dome Large Lights mounted driver and officer side Rear. N/A on E-One Chassis or two door commercial chassis. Required on Comm Chassis.	1	
5400-0150	Pump panel LED light package for side mount. Includes (6) Tecniq EON lights with S/S housings located (3) ea side. Includes S/S light shields (as applicable with intermedialte steps).	1	
MISC ELECTRICAL			
5110-0004	Alternating flasher for headlights.	1	
5110-0017	Back-up alarm 97 dB.	1	
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1	
LIGHTS - QUARTZ			
5450-0631-060	Light Whelen 12V Pioneer Plus flood LED model PFH1 powder coated white with external bottom raise pole. Includes switch accessible to driver. Location(s): officer side front compartment face.	1	
5450-0631-062	Light Whelen 12V Pioneer Plus flood LED model PFH1 powder coated white with external bottom raise pole. Includes switch accessible to driver. Location(s): driver side front compartment face.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			
8100-0089	All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	

Salescode	Extended Description	Qty	
EXTERIOR PAINT			
8100-0182-000-17	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint. Color: FLNA3225E-1 Red.	1	
8100-0442-000-17	International cab paint (by chassis OEM). Paint to match FLNA3225E-1 Red.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	
8300-0042	White rubrail scotchlite insert.	1	
8300-0146-000-J7	Chevron "A" style 6" 3M "Diamond Grade" striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0000	Standard 1 Year Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	
Dealer Supplied Equipment			

Commercial Pumper base bid price = \$336,317.00



Fire Apparatus Quotation for: METROPOLITAN AREA PLANNING COUNCIL



Quotation Number: 94891 Rev: 2

Unit Description: PMPR-TYPH

Quote Description: Pumper, Typhoon

Salesperson: AJACONETTI

Salescode	Extended Description	Qty	
TESTING COMPLIANCE STANDARD			
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3090-0007	Hosebed hoseload allowance on the apparatus shall be 1200 lbs.	1	
3340-1137-12B	Equipment allowance on the apparatus shall be 2000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
BUMPERS			
1160-0000	Bumper 10" stainless steel.	1	
1160-0008	3/16" Front Bumper Gravel Shield.	1	
1160-0014	20" Front Bumper Gravel Shield Extension.	1	
BUMPER TRAYS			
1150-0055	Hinged diamond plate lid for center bumper tray. Includes: seal, 1/4 turn latch and gas shock hold open device.	1	
1150-0121	Bumper tray center of bumper with slats 14 inches deep (approx 13 inches to slats).	1	
FRAME ASSEMBLY			
1250-0080	Frame assembly with 10.25 x 3.5 x .375 powder coated galvanized rails.	1	
1250-0085	Front chassis frame extensions, crossmembers and battery brackets shall be zinc plated (galvanized) IPOS. Includes rear subframe if applicable (urban interface, straight frame 4x4, etc).	1	
1250-0092	GEOMET coated frame assembly fasteners.	1	

Salescode	Extended Description	Qty	
AXLE OPTIONS			
1025-0017	Meritor RS-25-160 single rear axle 27,000 lb. capacity.	1	
1025-0029	Front shock absorbers.	1	
1025-0174	Meritor FL941 front axle 18,000 lb.	1	
SUSPENSIONS			
1070-0001	Rear suspension springs rated equal to the capacity of the axle.	1	
WHEEL OPTIONS			
1050-0000	Steel wheels for front axle (2).	1	
1050-0002	Steel wheels for rear axle (4).	1	
1050-0017	Each inside wheel of the single rear axle shall have valve stem extensions.	1	
TIRE OPTIONS			
1060-0016	Four Michelin 12R rear tires with XDN2 all weather tread.	1	
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1	
1060-0173	Two Michelin 315 tires model X Multiway 3D XZE for front axle.	1	
BRAKE SYSTEMS			
1100-0001	Meritor EX225H 17" disc brakes for front axle.	1	
1100-0002	ArvinMeritor 16-1/2" x 7" S-cam brakes with cast brake drums for a single rear axle.	1	
1100-0005	Brake system air 4X2/4X4.	1	
1100-0006	Parking brake release mounted on the driver's side lower dash.	1	
AIR SYSTEM OPTIONS			
1110-0000-001	Inlet for air system. Location: driver door jamb.	1	
1110-0002	Air dryer Bendix AD-9.	1	
1110-0006	Air lines nylon.	1	
1110-0041	Air horns Grover recessed in bumper (PR).	1	
ENGINES & TRANSMISSIONS			
1200-0017	Push-button transmission shift selector.	1	
1200-0020	TranSynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS3000.	1	
1200-0097	Electronic limiting of speed to 68 MPH maximum. Note: Max speed may be set at	1	

Salescode	Extended Description	Qty	
ENGINES & TRANSMISSIONS			
	65 MPH due to tire rating.		
1200-0340	Eng/Trans Cummins L9 400HP/EVS3000 2017 EPA compliant engine.	1	
SECONDARY BRAKING			
1125-0002	Jacobs engine compression brake.	1	
1125-0023	Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder.	1	
EXHAUST OPTIONS			
1225-0060	Exhaust end with fresh air vent for Plymovent exhaust extraction system.	1	
COOLING PACKAGE			
1800-0013	Cooling system for use with Cyclone II X, Typhoon X, and Quest chassis. For use with 2010 - 2018 EPA engines. Includes coolant recovery system.	1	
FUEL SYSTEMS			
1350-0005	Fuel system 65 gallons.	1	
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1	
1350-0022	Fuel line hose rubber.	1	
ALTERNATOR			
1700-0005	Alternator Leece Neville 320 amp. 320 amp SAE/272 amp NFPA.	1	
BATTERIES			
1400-0002	Battery four group 31 1000 CCA.	1	
CHASSIS OPTIONS			
1680-0005	Thermatic fan clutch.	1	
1680-0006	Drivelines 1710.	1	
1680-0008	Tow eyes front painted below bumper/cab (PR).	1	
1680-0011	Tow eyes rear below body, painted.	1	
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank. Location: left side below rear of cab.	1	
1680-0284	Radiator mounted power steering cooler.	1	
CAB MODEL			
1520-0013	Typhoon X medium cab with 58" CA	1	
CAB ROOF TYPE			

Salescode	Extended Description	Qty	
CAB ROOF TYPE			
1615-0010	Cab roof to be "flat" (non-vista).	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
GRILLE			
1620-0002	Stainless steel grille for Typhoon X.	1	
CAB DOOR OPTIONS			
1550-0003	Rear crew cab doors in the medium position.	1	
1550-0011	Rear crew cab door windows. Includes manual roll-down actuation. Not available on Typhoon or CII with paddle style door latching.	1	
1550-0017	Cab door panels stainless steel.	1	
1550-0025	All cab doors shall have "L" style exterior latches.	1	
1550-0027	Front cab door windows to have manual actuation.	1	
1550-0059-000-G6	Reflective Red/Lemon Yellow printed striping positioned in the "A" formation located on the cab door panels.	1	
1550-0077	Interior cab door locks - manual. Will have manual actuation from each respective door. Includes barrel style key lock on each exterior cab door.	1	
1550-0083	All cab exterior access doors to have CH751 keyed locks.	1	
1550-0186-659	(4) TecNiq T440 4" LED cab step area lighting. Locate each light on each cab door in the inboard position. Lights to be switched with door ajar.	1	
1550-0251	Driver and officer cab door windows - full glass style. For use with Typhoon and Cyclone cabs. Requires "L" handles and aluminum or S/S door panels.	1	
MIRRORS			
1670-0003	Velvac 2010 mirrors. Door mounted west coast style with remote control and heat.	1	
MISC EXTERIOR CAB OPTIONS			
1550-0020	Windows cab side fixed driver's side.	1	
1550-0033	Windows cab side fixed officer's side.	1	
1675-0022	Pair of 18" handrails located just behind driver and officer front door one each side.	1	
1675-0023	Pair of 18" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	

Salescode	Extended Description	Qty	
MISC EXTERIOR CAB OPTIONS			
1675-0047	Rear cab wall to be 3/16" aluminum diamond plate.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable brushed stainless steel.	1	
HVAC			
1515-0017	Air conditioning for the Typhoon X, CII X and Quest with Cummins ISC/ISL engine and radiator mounted condenser.	1	
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and CII with severe duty dash)	1	
SEATS			
1510-0004	Seats, Bostrom brand.	1	
1510-0008	Seat color gray.	1	
1510-0047	Officer seat to be Bostrom fixed SCBA.	1	
1510-0049	Driver seat to be Bostrom electric.	1	
1510-0054	Rear facing Bostrom seat with SCBA driver's side.	1	
1510-0057	Rear facing Bostrom seat with SCBA officer's side.	1	
1510-0063	Two man bench centered on rear wall with Bostrom SCBA. Includes angled corners.	1	
1510-0117-147	Bostrom SecureAll mechanical air pack bottle bracket (EA). Location: officer's seat.	1	
1510-0117-148	Bostrom SecureAll mechanical air pack bottle bracket (EA). Location: rear facing driver's side.	1	
1510-0117-215	Bostrom SecureAll mechanical air pack bottle bracket (EA). Location: rear facing officer's side.	1	
1510-0131-151	Bostrom SecureAll mechanical air pack bottle bracket (EA) for bench / fold-down seat. Location: inboard driver's side rear wall.	1	
1510-0131-152	Bostrom SecureAll mechanical air pack bottle bracket (EA) for bench / fold-down seat. Location: inboard officer's side rear wall.	1	
1510-0279-146	ReadyReach seat belt extender. Location: driver's seat.	1	
1510-0279-147	ReadyReach seat belt extender. Location: officer's seat.	1	
1510-0279-148	ReadyReach seat belt extender. Location: rear facing driver's side.	1	
1510-0279-151	ReadyReach seat belt extender. Location: inboard driver's side rear wall.	1	
1510-0279-152	ReadyReach seat belt extender. Location: inboard officer's side rear wall.	1	
1510-0279-215	ReadyReach seat belt extender. Location: rear facing officer's side.	1	

Salescode	Extended Description	Qty	
SEATS			
1510-0435	Seat cover low seam Durawear Plus (EA). Bostrom seats on bottom cushion only	6	
1685-0033	Seating capacity tag of six occupants.	1	
MISC INTERIOR CAB OPTIONS			
1685-0000	Cab interior gray. Does not include engine cover or seat color.	1	
1685-0006	Padded sun visors, driver and officer's side overhead.	1	
1685-0008	Control lanyard Y type for air horns.	1	
1685-0168	ABS Dash package. Includes center and officer side dash, lower kick panels and "A" post covers.	1	
1685-0187	Severe duty engine cover, molded polyurethane.	1	
1685-0496	ABS overhead console. Includes front full width overhead, air conditioning plenum and rear facing blower.	1	
1685-0531	Reduced profile rear engine cover for increased legroom.	1	
CAB ELECTRICAL OPTIONS			
1750-0022	Battery charger Kussmaul 40 amp model 1200 with air compressor.	1	
1750-0046-195	Cab Headlights. Position: lower.	1	
1750-0059-179-02	Receptacle inlet 20 amp with a Red cover. Location: outside driver's door next to handrail.	1	
1750-0072-546	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0072-593	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: officer side dash.	1	
1750-0075	English dominant main cab gauge cluster.	1	
1750-0158	Dome Lts Red/White LED. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wired through door and light assembly switch. Red light through light assembly switch.	1	
1750-0198-A31	Battery charger to be located behind driver's seat.	1	
1750-0199-A31	Air compressor to be located behind driver's seat.	1	
1750-0215-172	Turn signal Whelen M6 LED arrow amber pair located upper headlight bezel.	1	
1750-0429-546	Dual USB charging ports in the cab wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0429-593	Dual USB charging ports in the cab wired battery hot. Location: officer side dash.	1	
1750-0449	Momentary DPF regeneration override switch.	1	
1750-0514	Peterson LED cab headlights	1	

Salescode	Extended Description	Qty	
BODY COMPT LEFT SIDE			
3100-0096	Driver side body with full height 42" wide forward and 42" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well.	1	
BODY COMPT RIGHT SIDE			
3120-0005	Officer half side body with 42" wide forward and 42" wide rearward compartmentation. Includes adjustable ladder tracks.	1	
BODY COMPT REAR			
3110-0005	Full Height Rear Compartment. Includes smooth plate panels.	1	
3110-0034	Upper rear compartment depth to be shallow.	1	
3340-0116	Bolt-on diamond plate 14" tailboard (full width of body). Includes (2) squared off beavertails (no stanchions) with removable outer panels and handrails- (2) vertical on trailing edge of body and horizontal mounted handrail(s) below hosebed.	1	
DOORS			
3300-0105-003	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): L1.	1	
3300-0105-005	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): L3.	1	
3300-0105-027	Door roll up tall (greater than 45") with satin finish Amdor. Location(s): B1.	1	
3300-0106-004	Door roll up short (up to 45") with satin finish Amdor. Location(s): L2.	1	
3300-0106-015	Door roll up short (up to 45") with satin finish Amdor. Location(s): R1.	1	
3300-0106-016	Door roll up short (up to 45") with satin finish Amdor. Location(s): R2.	1	
COVERS			
3305-0003	Single diamond plate cover for the crosslay area. Includes applicable grab handle(s) and (2) butterfly style latches.	1	
3305-0004	Crosslay cover to be hinged forward.	1	
3305-0023	Nylon black cargo net at rear of diamond plate or vinyl hose bed cover or similar.	1	
3305-0025	Nylon black cargo net on sides for crosslay cover.	1	
3305-0033	Vinyl access cover for fill tower(s).	1	
3305-0034-000-02	Vinyl Red hose bed cover without rear flap(s). Requires rear cover option.	1	
3305-0119	Hold open device(s) for aluminum crosslay (single or bi-fold) cover. Locate as required based off options on module.	1	
PUMP MODULE			
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and tranverse module(s) if applicable.	1	

Salescode	Extended Description	Qty	
PUMP MODULE			
3130-0523	Side mount pump module. Extruded aluminum with runningboards.	1	
3130-0532	Pump panel opening is 39" wide. Pumper / tanker only.	1	
3130-0539	Pump module height is 75". Pumper / tanker only.	1	
PUMP PANELS			
3134-0016	Stainless steel driver and officer side pump panels.	1	
3134-0143	Officer side pump panel to be vertical hinged on forward extrusion. Panel to be (3) pieces with upper (2) panels secured in the closed position with push button latches. Upper panel to be held open with gas shock.	1	
MISC PUMP PANEL OPTIONS			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
PUMP MODULE OPTIONS			
3136-0000-202	Air horn switch at pump panel. Switch to be labeled "Evacuation Alert". Location: driver side pump panel.	1	
3136-0011	P-Rubber in flex joint(s) between pump module and/or body modules.	1	
3136-0058	E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels.	1	
3136-0138	Pump module storage pan.	1	
3136-0139	Crosslay double 7.5" wide each to hold up to 200' of 2.0" DJ hose (each).	1	
WATER TANK			
4010-0099	Fill tower(s) to be located offset to officer side of water tank.	1	
4010-0176	780 Gallon "T" Water Tank. UPF Poly III color fill towers. Note: Any foam cell(s) and/or storage options through the tank will reduce the overall water capacity.	1	
TANK PLUMBING			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0119	3" tank to pump Akron manual valve w/4" tank connection.	1	
LADDER STORAGE / RACKS			
3365-0025-515	Attic ladder mounting brackets (PR). Locate officer side compartment top.	1	
3365-0028	Hard Suction Storage Rack. Driver side compartment top. Includes spring hold downs and scuff plates behind spring mounts (as applicable).	1	
3365-0031	Hard Suction Storage Rack. Officer side in adjustable track above ladders (if applicable). Includes spring hold downs and scuff plates.	1	

Salescode	Extended Description	Qty	
LADDER STORAGE / RACKS			
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1	
3365-0087-C57	The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder.	1	
HANDRAILS / STEPS			
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
3330-0278	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on officer side (staggered stepped as applicable with tailboard depth) for additional hosebed access and handrail mounted on officer side upper hosebed side (as applicable).	1	
3330-0279-060	Innovative Controls dual lighted LED folding step. Location: officer side front compartment face. Each location requires a minimum of (1) handrail per NFPA.	1	
MISC BODY OPTIONS			
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion in the forward area and rearward area of the hose bed to run full width of the hosebed (as is practical with other hosebed mounted equipment).	1	
3340-0035	Divider Long. To run full length of hose bed (front to rear).	2	
3340-0058	Recessed fuel fill driver side wheel well.	1	
3340-0074	Body mainframe and hosebed side assemblies for a 85" high body.	1	
3340-0089-000-13	Turtle Tile Brand Black Floor Matting covering all applicable Compartment Floors, Shelves, and Rollout Trays. Does not include roof top compartments (Added separately)	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0486	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes.	1	
3340-0681	Body mainframe layout line to be 24". Includes body and all applicable modules.	1	
3340-1648	Anodized aluminum trim on bottom edge of all body compartment openings with painted edge.	1	
SCBA BOTTLE STORAGE			

Salescode	Extended Description	Qty	
SCBA BOTTLE STORAGE			
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
3320-0185-497	Fire Shopp brand (1) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location:driver side rear wheel well offset rearward	1	
3320-0186-498	Fire Shopp brand (2) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Location:officer side rear wheel well offset forward	1	
3320-0186-500	Fire Shopp brand (2) SCBA bottle storage with hinged door and push button latch. Door shall have a brushed stainless steel finish. Location:officer side rear wheel well offset rearward	1	
3320-0188-495	E-ONE designed Wheel Chock storage compartment driver side rear wheel well offset forward with hinged door and push button latch and wired to "Door Open" indicator inside cab. Door material to match wheel well material. Storage area shall hold (2) Zico Model SAC-44-E or comparable Wheel Chocks (not included).	1	
PUMPS			
4005-0030	Rating 1250 GPM	1	
4005-0195	Hale QFLO 750-1250 GPM pump, single stage. Requires primer option.	1	
PUMP CERTIFICATION			
4475-0000	Pump certification 750-2250 GPM	1	
PUMP OPTIONS			
4015-0008	Zinc anodes for Hale pump (PR), (1) discharge side and (1) intake side.	1	
4015-0016	Thermal relief valve, Hale TRVL-120.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0098	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location on pump panel.	1	
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1	
4015-0242	Trident primer W/3 barrel push button control. For use with 1250 GPM and larger pumps. Requires 15.6 CFM or larger engine air compressor.	1	
INTAKES			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	

Salescode	Extended Description	Qty	
INTAKE OPTIONS			
4445-0009	Intake relief valve, Akron.	1	
DISCHARGES AND PRECONNECTS			
4415-0008	1.5" Front bumper discharge Akron manual valve.	1	
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1	
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1	
4415-0022-350	2.5" Left Rear Discharge Akron Manual Valve. Location: left rear discharge.	1	
4415-0041	3" Deck Gun Discharge, Akron manual valve. (outlet shall terminate with MNPT threads unless extend gun is install)	1	
4415-0054-583	4" Right Pump Panel Discharge with 3" Akron Manual Valve (Waterous pumps noted location to be forward lower port). Location: right side discharge 1.	1	
4415-0178-532	Polished Stainless Steel Swivel Located on Top of Bumper officer's side of center tray for Front Bumper Discharge.	1	
4417-0106-L65	Deck gun piping to be positioned centered in deck gun channel.	1	
DISCHARGE OPTIONS			
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1	
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	9	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	
4417-0246	Dealer installed monitor, make and model as specified.	1	
PRESSURE GOVERNORS			
4465-0017	FRC PumpBoss pressure governor PBA400 series. Includes engine monitor gauges.	1	
GAUGES			
4435-0001	Class 1 Intelli-Tank water tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	9	
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	

Salescode	Extended Description	Qty	
ELECTRICAL SYSTEMS			
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1	
5010-0049	Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only.	1	
5010-0055-649	Vista IV display for V-MUX electrical system. Location: driver's side engine cover.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
5010-0100	AXIS Smart Truck Technology. Includes roof mounted antenna and 5 year data plan. For use only with E-ONE chassis in the USA.	1	
LIGHT BARS			
5300-0505	Whelen MK8H 5" high mount for front light bar (PR).	1	
5300-0506-000-4V	Front light bar LED color: Red/White with clear lenses (If applicable, includes side facing when colors are the same.)	1	
5300-0507	Light bar Whelen Freedom IV Model F4X7 72" with 14 LED modules. Location: Centered on the front cab roof.	1	
WARNING LIGHT PACKAGES			
5550-0149-534	Whelen M6 Super LED lower level warning light package. Includes (10) red M6R LED light heads w/chrome flanges. Locate side facing lights: at forward most position, centered in rear wheel well, and on side of beavertail.	1	
WARNING LIGHTS			
5600-0080-479-06	Whelen beacon with LED upper beacon and 700 series Super LED (PR) model B6LED with red domes and Red LEDs. Location: rear upper body on aerial style brackets.	1	
5600-0105-170	Hazard (door ajar) light 2" LED. Location: center overhead.	1	
5600-0301-469	Warning light Whelen M2 Super LED warning lights. Includes (2) red M2R LED light heads w/chrome flanges (if applicable). Location: (1) each side centered below forward compartments in rubrail if equipped.	1	
SIRENS			
5500-0015	Whelen model 295SLSA1 siren with microphone (replaced 295HFSA1).	1	
5500-0024-170	The primary electronic siren control is to be located center overhead.	1	
SPEAKERS			
5510-0029-B22	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: officer side front bumper inboard of frame.	1	
DOT LIGHTING			

Salescode	Extended Description	Qty	
DOT LIGHTING			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0025	Marker light Truck-Lite LED body/cab package. E-One custom cab and pumper or tanker body only.	1	
5150-0091	Whelen M6 series LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical 4 light housing and weatherproof connectors.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0276	Compartment light package TecNiq T440 4" LED for small bodies.	1	
5380-0280	Ground light package TecNiq T440 4" LED - large.	1	
LIGHTS - DECK AND SCENE			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0087-397	Whelen M6 Linear Super LED scene lights (PR). Switched in cab (lights mtd on the sides of apparatus to be switched separately). Locate (1) each side of cab, rearward of forward doors, up high.	1	
5390-0215-395	Deck Lights - Optronics Model TLL44 (PR). Location: rear body/beavertail area on the trailing edge up high.	1	
5390-0216	Hose bed light Optronics LED model TLL44 Locate at front of hose bed. Switched with work light switch in cab.	1	
5390-0217	Crosslay light Optronics LED model TLL44. Locate to rear of crosslay (SM) and forward of crosslay (TM as applicable). Switched with work light switch in cab.	1	
LIGHTS - NON-WARNING			
5400-0011	LED pump compartment light (EA).	1	
5400-0150	Pump panel LED light package for side mount. Includes (6) Tecniq EON lights with S/S housings located (3) ea side. Includes S/S light shields (as applicable with intermedialte steps).	1	
5400-0224	Engine compartment light Optronics LED Series ILL22 (EA).	1	
CONTROLS / SWITCHES			
5100-0042-276	Ramsey control with 3' cord for cab tilt in addition to standard toggle. Red/Black weatherproof push buttons at end of cord. Location of switch plug-in: next to manual cab tilt pump.	1	
5100-0165	Audible door ajar alarm wired through door ajar light. For use with multiplex display(s) only.	1	
MISC ELECTRICAL			

Salescode	Extended Description	Qty	
MISC ELECTRICAL			
5110-0004	Alternating flasher for headlights.	1	
5110-0017	Back-up alarm 97 dB.	1	
RECEPTACLES			
5470-0004-546	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			
8100-0089	All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0108	Front wheels to be painted on the inboard side (same color as outboard side).	1	
8100-0109	Rear wheels (4) to be painted on the inboard side (same color as outboard side). Includes outboard side of the inboard wheels.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-17	Paint E-ONE chassis cab - Sikkens paint. Color: FLNA3225E-1 Red.	1	
8100-0182-000-17	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint. Color: FLNA3225E-1 Red.	1	
8100-0186-000-39	Paint exterior surface of outer steel wheels. Sikkens paint. Color: Job Color.	1	
INTERIOR PAINT			
8150-0011	The interior of the cab to be painted Zolatone gray.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	
8300-0042	White rubrail scotchlite insert.	1	
8300-0084-000-G6	Chevron "A" style 6" printed sheet Scotchlite striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Lemon Yellow.	1	
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite	1	

Salescode	Extended Description	Qty	
STRIPING			
	diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.		
GRAPHICS			
8400-0067	E-ONE logo with grey backing on M6 series vertical tail light housing (PR).	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0000	Standard 1 Year Warranty.	1	
9100-0003	Lifetime Frame Structural Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	
9100-0090	25 Year frame rail corrosion warranty. Includes liners (if equipped).	1	
9100-0091	20 Year frame component corrosion warranty. Includes front frame extensions, crossmembers, battery tray brackets and rear underbody support (if applicable).	1	
9100-0101	Meritor 5 year unlimited miles, parts and labor front axle warranty for non-drive axle or a 2 year unlimited miles, parts and labor warranty for front drive axle.	1	
9100-0102	Meritor 5 year unlimited miles, parts and labor rear drive single or rear drive tandem axle warranty.	1	
Dealer Supplied Equipment			

Custom Pumper base bid price = \$473,289.00